

Eastto Axle Oils
GRADE: 60 (Light), 80 (Medium) & 100 (Heavy)

INTRODUCTION:

Eastto AXLE OILS are blended from refined base stocks having good thermal and oxidation stability with required load bearing and antiwear additives.

APPLICATION:



These oils are recommended for use in plain bearings and axle boxes of locomotives and wagons required by Railways and Steel Plants.

PERFORMANCE LEVEL: Meets IS: 1628 – 1986 Specification.

TYPICAL PROPERTIES:

TYPICAL PROPERTIES	60 (LIGHT)	EASTTO AXLE OILS 80 (MEDIUM)	100 (HEAVY)
Kinematic Viscosity at 60°C., cSt,	58 to 64	78 to 86	90 to 103
Viscosity Index, Min.	40	40	40
Flash Point, COC, °C, Min.	160	160	180
Pour Point, °C, Max.	-3	-3	-3

PACKING: 210 Litres Drum



Eastern Petroleum Private Limited

Regd. Off.:
Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg,
(Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India.
Tel.: +91 - 22 - 4232 4121, +91 - 22 - 2529 9990
Email: office@easternpetroleum.in, office@eastto.in,
Web: www.easternpetroleum.in, www.eastto.in



Eastern Petroleum Private Limited

an ISO 9001-2008 certified company



**Eastto
Axle Oils**