

PRODUCT DATA SHEET

PRODUCT: EASTTO BASE OIL.

INTRODUCTION: EASTTO BX-12, BX-32, BX-100, BX-120 are highly refined base STOCKS available in various viscosity range. These Oils are having excellent Chemical and Thermal Stability and having High Viscosity Index.

APPLICATION: EASTTO BX-12, BX-32, BX-100, BX-120 are used for manufacture Soluble and Neat Cutting Oils, Textile Lubricants such as Conning Oil, Antistatic Oil, Spin Finish Oil, Shoe Polish, Pigments, Transformer oils, Heat transfer oil, Metal working fluid, Rust preventive oils, Wire drawing oils, Agricultural Spray Oil, Mould Oil, Automotive lubricants, Flushing oil, Greases, White and paraffin oils, Printing inks and paints.



Cutting oils



Automotive Lubricants



Grease

TYPICAL PROPERTIES:

EASTTO BASE OIL					
Sr. No.	CHARACTERISTICS	Bx-12	Bx-32	Bx-100	Bx-120
1	Appearance	Clear	Clear	Clear	Clear
2	Flash Point °C, Min	160	190	210	220
3	Viscosity Index	--	95	95	95
4	Kinematic Viscosity @ 40°C, cst.	12	32	100	120
5	Pour Point °C, min	-6	-6	-6	-6
6	ASTM Colour, Max.	2.5	2.5	3.0	4.0
7	Inorganic Acidity	NIL	NIL	NIL	NIL

PACKING: 210 Litres Drums / Tanker Load.

Date of Issue : 20.12.2014

Date of Revision: 16.08.2016

These Characteristics are typical of current production while future production will confirm to **EASTERN PETROLEUM PVT. LTD.** Specification variation in these characteristics may occur.

