

PRODUCT DATA SHEET

PRODUCT: EASTTO COMPOUNDED FLUIDS

GRADES: 460, 1000

INTRODUCTION: These bituminous lubricants are available in two grades with different ranges of viscosities from heavy oil to a semi-solid at normal ambient temperatures. These compounded fluids are normally used neat or can be diluted with a high flash solvent for easier applications. They have excellent extreme pressure properties, very high adhesive characteristics and good low temperature properties with wide operating temperature range.

APPLICATION: They are recommended for the lubrication of wire ropes, chains, flexible couplings, gears, and sliding surfaces of drag lines and shovel. These lubricants can also be used in Open gears of mine hoists, Ball mills, Rubber mixers, Cement mills, Clay product industries, Sugar mill industry, Construction equipment, Dredging equipment as well as other applications where a heavy adhesive lubricant is required.



Lubrication of Wire ropes, Chains, Flexible couplings etc.

TYPICAL PROPERTIES

CHARACTERISTICS	EASTTO COMPOUNDED FLUIDS	
	460	1000
Colour	Black	Black
Kinematic Viscosity at 100°C, cSt	460	1000
Flash Point (COC) °C. Min.	210	220

PACKING: 180 Kgs Drum

Date of issue : 13.09.2014

Date of Revision: 05.08.2016

1st Revision: 29.05.2019 (CK)

PDS No. 20730 – 20731





Eastern Petroleum Pvt. Ltd.

an ISO 9001-2008 certified company

Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg,
(Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India.

Tel.: +91 - 22 - 4232 4121, 2529 9990,

Email: office@easternpetroleum.in, Web: www.easternpetroleum.in

CIN NO:U24100MH1964PTC012931

These Characteristics are typical of current production while future production will confirm to **EASTERN PETROLEUM PVT. LTD.**
Specification variation in these characteristics may occur.

