

## Eastto Compounded Fluids

GRADES: 460 & 1000

### INTRODUCTION:

**Eastto** COMPOUNDED FLUIDS are available in two grades with different ranges of viscosities from heavy oil to a semi-solid at normal ambient temperatures. These compounded fluids are normally used neat or can be diluted with a high flash solvent for easier applications. They have excellent extreme pressure properties, very high adhesive characteristics and good low temperature properties with wide operating temperature range.

### APPLICATION:

They are recommended for the lubrication of wire ropes, chains, flexible couplings, gears, and sliding surfaces of drag lines and shovel. These lubricants can also be used in open gears of mine hoists, ball mills, rubber mixers, cement mills, clay product industries, construction equipment, dredging equipment as well as other applications where a heavy, adhesive lubricant is required.

TYPICAL PROPERTIES	EASTTO COMPOUNDED FLUIDS	
	460	1000
Colour	Black	Black
Kinematic Viscosity at 100°C, cSt	440 - 480	980 - 1020
Flash Point, COC, °C, Min.	210	220
Copper Corrosion Test at 100°C for 3 Hours, Max.	1	1

**PACKING:** 180 Kgs Drum



### Eastern Petroleum Private Limited

#### Regd. Off.:

Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg,  
(Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India.  
Tel.: +91 - 22 - 4232 4121, +91 - 22 - 2529 9990  
Email: office@easternpetroleum.in, office@eastto.in,  
Web: www.easternpetroleum.in, www.eastto.in



Eastern Petroleum Private Limited

an ISO 9001-2008 certified company



## Eastto Compounded Fluids