

## PRODUCT DATA SHEET

**PRODUCT:** **EASTTO COMPRESSOR OILS**

**GRADES:** **32, 46, 68, 100, 150, 220, 320**

**INTRODUCTION:** **EASTTO COMPRESSOR OILS - 32, 46, 68, 100, 150, 220, and 320** are blended from highly refined based stocks with antioxidant and rust inhibitor. They provide excellent lubrication under high temperature and high load conditions.

**APPLICATION:** **EASTTO COMPRESSOR OILS - 32, 46, 68, 100, 150, 220 and 320** are recommended for cylinder lubrication of reciprocating compressors and rotary air compressor operating up to 220°C air discharge temperature. It can be used for vacuum pump, Circulating systems and Hydraulic systems.



**PERFORMANCE LEVEL:** Meet requirements of cylinder lubricants in reciprocating and rotary air compressors.

### TYPICAL PROPERTIES:

CHARACTERISTICS	EASTTO COMPRESSOR OILS						
	32	46	68	100	150	220	320
Kinematic Viscosity at 40°C, cSt.	32	46	68	100	150	220	320
Viscosity Index	95	95	95	95	95	95	95
Flash Point, COC, °C	190	190	200	200	210	220	220
Pour Point, °C	-6	-6	-6	-6	-6	-6	-6

**PACKING:** 210 Litres Drum

**Date of Issue** : 13.09.2014

**Date of Revision:** 05.08.2016

**1<sup>st</sup> Revision:** 29.05.2019 (CK)

**PDS No.** 03.23.01 – 03.23.07





**Eastern Petroleum Pvt. Ltd.**

an ISO 9001-2008 certified company

Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg,  
(Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India.

Tel.: +91 - 22 - 4232 4121, 2529 9990,

Email: office@easternpetroleum.in, Web:www.easternpetroleum.in

CIN NO:U24100MH1964PTC012931

These Characteristics are typical of current production while future production will confirm to **EASTERN PETROLEUM PVT. LTD.**  
Specification variation in these characteristics may occur.

