

Eastern Petroleum Pvt. Ltd.

an ISO 9001-2008 certified company Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg, (SionTrombay Road), Chembur, Mumbai - 400 071. MH, India. Tel.: +91 - 22 - 4232 4121, 2529 9990, Email: office@easternpetroleum.in, Web:www.easternpetroleum.in CIN NO:U24100MH1964PTC012931

MATERIAL SAFETY DATA SHEET

1. Product name and Company identification

Product Name	:	EASTTO CONKUT EX, CX
Product Use	:	Emulsifier for soluble cutting oil
Supplier	:	Eastern Petroleum Pvt. Ltd 235-239, Jawahar Industrial Estate, Kamothe, Panvel, Dist- Raigad, Maharashtra: 410209
Telephone No.	:	91-22-2743 1694, 91-22-2743 3819.
Email	:	sales@easternpetroleum.in

2. Composition / Information of Ingredients

	Ingredient name	CAS Number	% by wt
	Highly refined mineral base oil Proprietary additives Water	64742-65-0 mixture 	30 - 40 60 - 65 5 - 10
3.	Hazards identification	Non dangerous substance	
	Physical state	Liquid	
	Human Health Effects		
	Eyes	May cause mild irritation only if directly conta	ct with eyes.
	Skin	Not expected to cause skin irritation.	
	Inhalation	Not expected to cause any side effect while in	nhalation.
4.	First Aid Measures		
	Inhalation	If inhaled, remove to fresh air. Get medical at	tention if symptoms occur.
	Skin contact	Immediately wash affected area with soap clothing and shoes. Get medical attentions if	
	Eye contacts	In case of contact immediately wash eyes wit	

Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If potentially dangerous quantities of this material have been swallowed, call a physician immediately. Get medical attention if symptoms occur.

5. Fire-fighting Measures

Ingestion

Flammability of product	Non Combustible liquid
Extinguishing Media Suitable Not suitable	Use dry chemical, carbon dioxide (CO ₂), or foam Do not use water.

6. Accidental Release Measures

Personal precautions	Wear suitable protection clothing and equipment. Remove contaminated clothes as soon as possible.
Environmental precautions	Prevent from spreading or entering into drains, ditches or rivers by using sand, earth or other appropriate barriers. Inform local authorities if this cannot be prevented. Pick up free liquid for recycling or disposal. The residual oil can be transferred to another container.



Eastern Petroleum Pvt. Ltd.

an ISO 9001-2008 certified company Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg, (SionTrombay Road), Chembur, Mumbai - 400 071. MH, India. Tel.: +91 - 22 - 4232 4121, 2529 9990, Email: office@easternpetroleum.in, Web:www.easternpetroleum.in CIN NO:U24100MH1964PTC012931

Clean up method- small spillage	Absorb liquid with sand or earth, sweep up and remove to a suitable, clearly marked container for disposal in accordance with local regulation.
Clean up methods – large spillage	Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Dispose of as for small spills.

7. Handling and Storage

Handling

Storage

Handle in accordance with good industrial hygiene and safety practices. If handled at elevated temperatures or with high speed mechanical equipment, vapours or mists might be released and require a well ventilated workplace. Store at ambient temperature or with lowest necessary heating as required for ease of handling.

8. Exposure Controls / Personal Protection

Control parameters	Use well ventilated area where the material is heated or sprayed
Personal protection equipment	
Respiratory protection Hand protection Eye protection Skin and body protection Hygienic measures	Avoid inhalation use suitable mask with filter if necessary. Wear oil-resistant protective gloves if there is a risk of skin contact. For eyes protection wear safety goggles. Use protective cloths and gloves. Act in accordance with good industrial Hygiene and safety practice.

9. Physical and Chemical Properties

CHARCTERISTICS	EASTTO CONKUT EX	EASTTO CONKUT CX
Physical state	Viscous liquid	Viscous liquid
Odour	Mild	Mild
Sp. Gravity @ 30 °C gm/ml	1.03	1.03
Kinematic viscosity @ 100 °C, cst	30	30
Colour	Dark brown	Dark brown
Solubility in water	Soluble	Soluble
pH(5% Emulsion in DM water)	9.3	9.3

10. Stability and Reactivity

normal conditions and decompose at higher temperature.
e heating and highly oxidizing agents
s decomposition products are not expected to form during normal
ation will not occur
J

11. Toxicological Information

Potential chronic health effects Carcinogenicity

No known significant effects or critical hazards.

12. Ecological Information

Environment effect:

Will not have chronic effect on aquatic environment

13. Disposal considerations

Waste disposal procedure:

Place contaminated materials in a disposable container and dispose of in accordance with Local, State environmental regulations and contact local environment and health authorities to get the permission for waste disposal.

14. Transport Information EASTTO CONKUT EX, CX Revision No. 3 Not classified as hazardous for transport (DOT, TDG, IMO/IMDG, IATA/ICAO)

Date of issue: 24.12.2014 Date of revision: 25.08.2016



Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg, (SionTrombay Road), Chembur, Mumbai - 400 071. MH, India. Tel.: +91 - 22 - 4232 4121, 2529 9990, Email: office@easternpetroleum.in, Web:www.easternpetroleum.in CIN NO:U24100MH1964PTC012931

15.	Regulatory Information	Not classified as hazardous.
16.	Other Information	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information, and belief at the date of its publication. The information given is designed as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material in combination with any other materials or in any process, unless specified in the text.