

Eastern Petroleum Pvt. Ltd.

an ISO 9001-2008 certified company Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg, (Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India. Tel.: +91 - 22 - 4232 4121, 2529 9990, Email: office@easternpetroleum.in, Web:www.easternpetroleum.in CIN NO: U24100MH1964PTC012931

PRODUCT DATA SHEET

PRODUCT:

INTRODUCTION:

EASTTO CONNING OIL 10

EASTTO CONING OIL10 is emulsifiable oil and has been formulated from highly refined mineral oils and specially selected surface active agents to provide appropriate antistatic property. This oil is non-staining, with good emulsion stability and excellent antistatic properties.

APPLICATION:

EASTTO CONING OIL 10 is used for all texturising / twisting / crimping operations for synthetic yarns. It is also used for softening and wetting of yarn during woolen, rayon cording and rayon conning operation.







PERFORMANCE LEVEL:

EASTTO CONING OIL 10 is a proprietary grade.

TYPICAL PROPERTIES:

CHARACTERISTICS	EASTTO CONNING OIL 10
Kinetic Viscosity at 40°C., cst	10
Colour, ASTM, Max.	1.0
Flash Point, COC, ºC	150
Emulsion Stability Test for 24 Hrs.	Passes

PACKING: 210 Litres Drums

Date of issue: 10.11.2014

Date of revision: 24.08.2016

PDS No. 04.01.01

These Characteristics are typical of current production while future production will confirm to **EASTERN PETROLEUM PVT. LTD.** Specification variation in these characteristics may occur.

