

PRODUCT DATA SHEET

PRODUCT: EASTTO GAS ENGINE OIL SAE 40, 20W-50

INTRODUCTION: EASTTO GAS ENGINE OIL SAE 40, 20W-50 are high performance premium quality Gas Engine Oils with medium ash content for light vehicles running on Compressed Natural Gas (CNG) and Liquefied Petroleum Gas (LPG). These oils have extended oil life due to excellent oxidation resistance. Medium ash content prolongs the life of the exhaust valves and spark plugs and keeps the pistons and engine clean for smooth operation. These oils are also compatible with catalytic converter fitted in the exhaust system of vehicles.

APPLICATION: EASTTO GAS ENGINE OIL SAE 40, 20W-50 are recommended for use in light vehicles, Auto rickshaws, Taxis, Cars, Buses, etc. running on Compressed Natural Gas (CNG) and Liquefied Petroleum Gas (LPG).



Engine Oils with medium ash content for light and heavy vehicles.

PERFORMANCE LEVEL: Meets the performance level of API CD /SF, IS: 13656-2002, EDL-2

TYPICAL PROPERTIES

CHARACTERISTICS	EASTTO GAS ENGINE OIL SAE 40	EASTTO GAS ENGINE OIL SAE 20W-50
Kinematic Viscosity at 100°C, cst	14	18.5
Flash Point, COC, °C, Min.	220	220
Pour Point, °C	-9	-21
Sulphated Ash, % Wt., Max.	1.0	1.0

PACKING: 210 Liters Drums

Date of issue: 04.09.2014

Date of revision: 26.08.2016

PDS No. 01.19.01 – 01.19.02

These Characteristics are typical of current production while future production will confirm to **EASTERN PETROLEUM PVT. LTD.** Specification variation in these characteristics may occur.

