

## PRODUCT DATA SHEET

**BRAND:** EASTTO INDUSTRIAL GEAR OILS

**GRADES:** VG 68, 100, 150, 220, 320, 460, 680

**INTRODUCTION:** These Oils are blended from highly refined Base Stocks and are fortified with specially selected EP additives. They have good thermal stability and high oxidation resistance, good demulsibility, low foaming tendency and provide rust and corrosion protection to metal surfaces.

**APPLICATION:** These Oils are recommended for heavy duty enclosed Spur, Bevel, Helical, Herringbone and Planetary gear drives with Splash and Circulation systems and for Plain Bearings, Sliding surfaces & Chain drives subjected to heavy shock loads where temperatures do not exceed 100°C.



These Oils are recommended for heavy duty Gear drives, Chain drives and for Plain bearings.

**PERFORMANCE LEVEL:** Meets IS: 8406 – 1993 (RA 2006) requirements.

### TYPICAL PROPERTIES:

EASTTO INDUSTRIAL GEAR OILS							
CHARACTERISTICS	68	100	150	220	320	460	680
Kinematic Viscosity @ 40°C cst	68	100	150	220	320	460	680
Viscosity Index	95	95	95	95	95	95	95
Flash Point (COC) °C	200	210	210	215	220	220	230
Pour Point, °C	-6	-6	-6	-6	-6	-6	-6

**PACKING:** 210 Litres Drums

**Date of issue :** 14.09.2014

**Date of Revision:** 05.08.2016

**1<sup>st</sup> Revision:** 29.05.2019 (CK)

**PDS No.** 03.21.01 – 03.21.07

These Characteristics are typical of current production while future production will confirm to **EASTERN PETROLEUM PVT. LTD.** Specification variation in these characteristics may occur.





**Eastern Petroleum Pvt. Ltd.**

an ISO 9001-2008 certified company

Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg,  
(Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India.  
Tel.: +91 - 22 - 4232 4121, 2529 9990, Fax: +91 - 22 - 4232 4131, 2524 1895  
Email: [office@easternpetroleum.in](mailto:office@easternpetroleum.in), Web: [www.easternpetroleum.in](http://www.easternpetroleum.in)  
CIN NO: U24100MH1964PTC012931

