

## Eastto Hydraulic Oils AW

Grades:

VG 32, 46, 57\*, 68, 100 AND 150

### Introduction:

**Eastto** HYDRAULIC OILS AW are blended from highly refined base stocks with high viscosity index and specially selected anti-oxidant, anticorrosion, anti-wear, anti-rust and anti-foam additives. These oils can sustain very high pressure of the system and high speed of the pumps, and compatible with the seals normally used in the hydraulic system.

### Application:

EASTTO HYDRAULIC OILS AW are recommended where long service life and a wide variety of industrial hydraulic and circulation systems are required.

### Performance Level:

IS: 10522:1983 [Reaffirmed November, 1998]

### Typical properties

Characteristics	EASTTO HYDRAULIC OILS HLP				
	32	46	68	100	150
KV at 40°C	30 – 34	44 – 48	66 – 70	95 – 105	145 – 155
VI, Min.	95	95	95	95	95
Flash Point, COC, °C. Min	190	210	210	220	220
Pour Point, °C. Max.	-6	-6	-6	-6	-6

**Packing:** 210 Litres Drum

Date of issue: 23.09.2014  
PDS No. 03.04.01 – 03.04.05



Eastern Petroleum Private Limited

an ISO 9001-2008 certified company



## Eastto Hydraulic Oils HLP



### Eastern Petroleum Private Limited

#### Regd. Off.:

Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg,  
(Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India.  
Tel.: +91 - 22 - 4232 4121, +91 - 22 - 2529 9990  
Email: office@easternpetroleum.in, office@eastto.in,  
Web: www.easternpetroleum.in, www.eastto.in

