

## PRODUCT DATA SHEET

**PRODUCT:** EASTTO HYDRAULIC OILS HLP

**GRADE:** VG 32, 46, 68, 100, 150

**INTRODUCTION:** EASTTO HYDRAULIC OILS HLP are premium grade hydraulic oils having extra heavy duty anti-wear property with excellent thermal stability and high FZG rating. They have excellent compatibility with seals normally used in hydraulic system and unique hydrolytic stability.

**APPLICATION:** EASTTO HYDRAULIC OILS HLP are recommended for high performance electro-hydraulic or numerically systems. These oils can be used for chain drives and compressor crankcase lubrication. It is also being used in on and off-highway industries including: Trucking, Construction, Mining, Quarrying, and Agriculture.



**PERFORMANCE LEVEL:**

IS: 10522:1983 [Reaffirmed 2004] DIN 51524 Part II

### TYPICAL PROPERTIES

EASTTO HYDRAULIC OILS HLP					
Characteristics	32	46	68	100	150
Kinematic viscosity @ 40°C, cst	32	46	68	100	150
Viscosity Index	99	104	104	105	110
Flash Point, (COC) °C	200	205	210	220	230
Pour Point, °C.	-6	-6	-6	-6	-6

**PACKING:** 210 Litres Drums.

**Date of issue** : 13.09.2014

**Date of Revision:** 06.08.2016

**1<sup>st</sup> Revision:** 29.05.2019 (CK)

**PDS No.** 03.04.01 – 03.04.05

These Characteristics are typical of current production while future production will confirm to **EASTERN PETROLEUM PVT. LTD.** Specification variation in these characteristics may occur.

