Eastto BASE Low Visc PX-3

INTRODUCTION: East to Base Oil PX-3 is used along with resins dyes, etc. This is a transparent light coloured products having varied solvency. This is highly refined paraffinic hydrocarbon fractions having excellent oxidation and chemical stability with high flash points.

APPLICATION: Eastto Base Oils PX-3 can be used as diluents in many industrial applications, such as Metal Working Fluids, Water Treatment Chemicals, Silicone, Sealants, Cosmetic, Polishes, Varnishes and as a lubricant in Rubber minute machine parts.

PERFORMANCE LEVEL:

TYPICAL PROPERTIES

CHARACTERISTICS	EASTTO LOW VISCOSITY BASE OIL PX-3
Appearance	Clear Liquid
Colour, ASTM Max	Colourless
Density @ 29.5 Deg C gm/ml.	0.811
Kinematic Viscosity @ 40 Deg C, cSt.	3.53
FBP Deg C	322
IBP Deg C	258
Flash Point, COC Deg C	126
Pour Point Deg C	-18
Aniline Point Deg C	91
Water Content	16 ppm
Aromatic Content	50 ppm
Refractive Index at 20 Deg C	1.45

PACKING: 210 Litres Drums










Eastern Petroleum Private Limited

Regd. Off.:

Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg, (Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India. Tel.: +91 - 22 - 4232 4121, +91 - 22 - 2529 9990 Email: office@easternpetroleum.in, office@eastto.in, Web: www.easternpetroleum.in, www.eastto.in





an ISO 9001-2008 certified company



EasttoEastto Low Visc PX- 3