Eastto EASTTO MAX SERIES (PARAFFINIC RICH LOW AROMATIC SOLVENTS)

INTRODUCTION: EASTTO MAX SERIES are chemically processed specially formulated solvents, free from aromatics and unsaturated hydrocarbons. These are odourless, clear and colourless liquid.

APPLICATION: These products are widely used in manufacture of Polish, Metal degreasing products, Specialty lubricants, Agrochemicals, Paints, Printing inks, Rust preventives, Aerosols, Ultra sonic cleaning agent, Thinner, Lube oil additives, Pesticides, Insecticide, Specialty chemicals, Fuel additive, Drilling fluid, Mosquito repellents and a solvent for industrial application.

TYPICAL PROPERTIES

PROPERTIES	EASTTO MAX- A	EASTTO MAX- 65	EASTTO MAX- 80	EASTTO MAX- 110
Appearance	Bright & Clear Liquid			
Odour	Odourless	Odourless	Odourless	Odourless
Specific Gravity @ 29.5°C	0.77	0.78	0.77	0.78
Acidity	Nil	Nil	Nil	Nil
Flash Point (PMCC) °C	65	70	96	109
Kinematic Viscosity@40°C,cst	1.7	1.2	1.5	1.4
Aromatics	Less than 1%	Less than 1%	Less than 1%	Less than 1%
Boiling Range – IBP °C	180	171	205	240
FBP °C	240	222	266	277









Eastern Petroleum Private Limited

Road Off

Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg, (Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India. Tel.: +91 - 22 - 4232 4121, +91 - 22 - 2529 9990 Email: office@easternpetroleum.in, office@eastto.in, Web: www.easternpetroleum.in, www.eastto.in





Eastern Petroleum Private Limited

an ISO 9001-2008 certified company







Eastto

Eastto Max Series

[paraffinic Rich Low Aromatic Solvent]