



Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg, (Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India.
Tel.: +91 - 22 - 4232 4121, 2529 9990, Fax: +91 - 22 - 4232 4131, 2524 1895
Email: office@easternpetroleum.in, Web:www.easternpetroleum.in
CIN NO:U24100MH1964PTC012931

PRODUCT DATA SHEET

PRODUCT:	EASTTO MORGAN BEARING OILS
GRADE:	VG 100, 150, 220,320, 460
INTRODUCTION:	EASTTO MORGAN BEARING OILS 100, 150, 220,320, 460 are specially premium quality heavy duty bearing oils with superior oxidation and good thermal stability. They have unique demulsibility, Anti-foaming, Anti-oxidation, Anti-rust characteristics and excellent film strength property to minimize wear in roll-neck bearings of steel mills.
APPLICATION:	EASTTO MORGAN BEARING OILS 100, 150, 220,320, 460 are recommended for the Morgan bearings of steel mills, Plate Mills, Wire Rod Mills, Merchant Mills, Blooming and Billet Mills, Rail and Structural Mills with various viscometric grades to take care of heavier load in the presence of water.







PERFORMANCE LEVEL: Meet requirements of Morgan Bearing Lubricant specified by Morgan Construction Co., USA and

IPSS: 1-09-001-81

TYPICAL PROPERTIES:

EASTTO MORGAN BEARING OILS						
CHARACTERISTICS	100	150	220	320	460	
Kinematic Viscosity at 40°C, cst	100	150	220	320	460	
Viscosity Index	95	95	95	95	95	
Flash Point (COC), °C	210	210	220	220	250	
Pour Point, °C	-6	-6	-6	-6	-6	

PACKING: 210 Litres Drum

Date of issue : 14.09.2014 Date of Revision: 27.02.2017 1st Revision: 29.05.2019 (CK)

PDS No. 03.50.01 - 03.50.05

These Characteristics are typical of current production while future production will confirm to **EASTERN PETROLEUM PVT. LTD.** Specification variation in these characteristics may occur.

