Eastto PET 1400- Magnesium Petroleum Sulphonate

INTRODUCTION: EASTTO PET 1400 is manufactured from Sulphonic acid, produced from synthetic base stock and neutralized with Magnesium Hydroxide. The Magnesium Petroleum Sulphonate enables the product to provide rust protection.

APPLICATION: It is used in the manufacture of Engine Oils and Industrial Lubricants. It also works as a detergent type Additive. It is also used in Fuel Additives, which helps in better combustion of Fuel in Engine and thus Soot Formation is reduced in the system

PERFORMANCE LEVEL: Proprietary product

TYPICAL PROPERTIES

CHARACTERISTICS	EASTTO PET 1400
Appearance	Dark Brown Viscous Liquid
Specific Gravity @ 15.6 / 15.6°C	1 – 12
Magnesium, Wt. %	8-9.60
TBN, mgKOH/gm.	380-400
K. Viscosity @ 100° C, cSt.	50
Flash Point, (PMCC), Min.	140

PACKING: 200 Kgs of M.S. Barrels.









Eastern Petroleum Private Limited

Road Off

Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg, (Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India. Tel.: +91 - 22 - 4232 4121, +91 - 22 - 2529 9990 Email: office@easternpetroleum.in, office@eastto.in, Web: www.easternpetroleum.in, www.eastto.in





Eastern Petroleum Private Limited

an ISO 9001-2008 certified company



Eastto
PET 1400
Magnesium Petroleum Sulphonate