



Eastern Petroleum Pvt. Ltd.

an ISO 9001-2008 certified company

Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg,
(Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India.

Tel.: +91 - 22 - 4232 4121, 2529 9990,

Email: office@easternpetroleum.in, Web: www.easternpetroleum.in

CIN NO: U24100MH1964PTC012931

MATERIAL SAFETY DATA SHEET

1. Product name and Company identification

Product Name	:	EASTTO PET 1400 (MAGNESIUM PETROLEUM SULPHONATE)
Product Use	:	Corrosion inhibitor
Supplier	:	Eastern Petroleum Pvt. Ltd 235-239, Jawahar industrial Estate, Kamothe, Panvel, Dist- Raigad, Maharashtra: 410209
Telephone No.	:	91-22-2743 1694, 91-22-2743 3819.
Email	:	sales@easternpetroleum.in

2. Composition / Information of Ingredients

Ingredient name	CAS Number	% by wt
Magnesium Petroleum Sulphonate	61789-87-5	60 – 65
Water	7732-18-15	0.5 – 1.0
Alkalate	68515-32-2	Balance

3. Hazards identification

	Non dangerous substance
Physical state	Viscous liquid
Human Health Effects	
Eyes	May cause mild irritation only if directly contact with eyes.
Skin	Not expected to cause skin irritation.
Inhalation	Not expected to cause any side effect while inhalation.

4. First Aid Measures

Inhalation	If inhaled, remove to fresh air. Get medical attention if symptoms occur.
Skin contact	Immediately wash affected area with soap and water. Remove contaminated clothing and shoes. Get medical attentions if a symptom occurs.
Eye contacts	In case of contact immediately wash eyes with plenty of water.
Ingestion	Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If potentially dangerous quantities of this material have been swallowed, call a physician immediately. Get medical attention if symptoms occur.

5. Fire-fighting Measures

Flammability of product	Not combustible
Extinguishing Media Suitable	Use dry chemical, carbon dioxide (CO ₂), or foam
Not suitable	Do not use water.

6. Accidental Release Measures

Personal precautions	Wear suitable protection clothing and equipment. Remove contaminated clothes as soon as possible.
Environmental precautions	Prevent from spreading or entering into drains, ditches or rivers by using sand, earth or other appropriate barriers. Inform local authorities if this cannot be prevented. Pick up free liquid for recycling or disposal. The residual oil can be transferred to another container.

Clean up method- small spillage Absorb liquid with sand or earth, sweep up and remove to a suitable, clearly marked container for disposal in accordance with local regulation.

Clean up methods – large spillage Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Dispose of as for small spills.

7. Handling and Storage

Handling Handle in accordance with good industrial hygiene and safety practices. If handled at elevated temperatures or with high speed mechanical equipment, vapors or mists might be released and require a well ventilated workplace.

Storage Store at ambient temperature or with lowest necessary heating as required for ease of handling.

8. Exposure Controls / Personal Protection

Control parameters Use well ventilated area where the material is heated or sprayed

Chemical name Magnesium Petroleum Sulphonate

Personal protection equipment

Respiratory protection Avoid inhalation use suitable mask with filter if necessary.

Hand protection Wear oil-resistant protective gloves if there is a risk of skin contact.

Eye protection For eyes protection wear safety goggles.

Skin and body protection Use protective cloths and gloves.

Hygienic measures Act in accordance with good industrial Hygiene and safety practice.

9. Physical and Chemical Properties

CHARACTERISTICS	EASTTO PET 1400
Physical state	Viscous liquid
Odour	Mild
Colour	Dark brown
Solubility in water	Negligible
Flash point °C	>140

10. Stability and Reactivity

Reactivity and stability Stable at normal conditions and decompose at higher temperature.

Conditions to avoid Excessive heating and highly oxidizing agents

Hazardous decomposition products Hazardous decomposition products are not expected to form during normal storage.

Hazardous polymerization Under normal conditions of storage and use, polymerization will not occur.

11. Toxicological Information

Potential chronic health effects

Carcinogenicity No known significant effects or critical hazards.

12. Ecological Information

Environment effect:

Will not have chronic effect on aquatic environment

13. Disposal considerations

Waste disposal procedure:

Place contaminated materials in a disposable container and dispose of in accordance with Local, State environmental regulations and contact local environment and health authorities to get the permission for waste disposal.



Eastern Petroleum Pvt. Ltd.

an ISO 9001-2008 certified company

Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg,
(Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India.

Tel.: +91 - 22 - 4232 4121, 2529 9990,

Email: office@easternpetroleum.in, Web: www.easternpetroleum.in

CIN NO: U24100MH1964PTC012931

14. Transport Information	Not classified as hazardous for transport (DOT, TDG, IMO/IMDG, IATA/ICAO)
15. Regulatory Information	Not classified as hazardous.
16. Other Information	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information, and belief at the date of its publication. The information given is designed as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material in combination with any other materials or in any process, unless specified in the text.