

PRODUCT DATA SHEET

PRODUCT:
EASTTO PET 1400 - MAGNESIUM PETROLEUM SULPHONATE
INTRODUCTION:

EASTTO PET 1400 is manufactured from Sulphonic acid, produced from synthetic base stock and neutralized with Magnesium Hydroxide. The Magnesium Petroleum Sulphonate enables the product to provide rust protection.

APPLICATION:

It is used in the manufacture of Engine Oils and Industrial Lubricants. It also works as a detergent type Additive. It is also used in Fuel Additives, which helps in better combustion of Fuel in Engine and thus Soot Formation is reduced in the system


PERFORMANCE LEVEL:

Proprietary product

TYPICAL PROPERTIES:

CHARACTERISTICS	EASTTO PET 1400
Appearance	Dark Brown Viscous Liquid
Specific Gravity @ 15.6 / 15.6°C	1 to 12
Magnesium, Wt. %	8- 9.60
TBN, mgKOH/gm.	380- 400
K. Viscosity @ 100° C, cSt.	50
Flash Point, (PMCC), Min.	140

PACKING: 200 Kgs of M.S. Barrels.

Date of issue : 24.12.2014

Date of Revision: 09.08.2016
PDS No. 20.06.01

These Characteristics are typical of current production while future production will confirm to **EASTERN PETROLEUM PVT. LTD.** Specification variation in these characteristics may occur.

