

## PRODUCT DATA SHEET

**PRODUCT:** EASTTO WAX 10 & 20

**GRADES:** POLYPROPYLENE WAX

**INTRODUCTION:** Waxes are low melting inert products usually snow white in colour. These could be of natural origin e.g. bees wax or synthetics e.g. polypropylene wax etc. Then there are paraffin waxes- a bye-product of base oil manufactured from petroleum crude or microcrystalline waxes which are removed from base oils for lowering their pour point.

**APPLICATION:** Used as additives to improve the melting point of formulations. Have excellent water proofing properties, provide film strength capability, lubricity and wear protection. Used with profit in anti-sound special purpose greases together with MoS<sub>2</sub> where water washing resistance is desired. It can also be useful for paints and pigments.



Widely used in Paints and grease

**TYPICAL PROPERTIES:** (Testing carried out as per relevant BP/ASTM standards):

CHARACTERISTICS	EASTTO WAX-10	EASTTO WAX- 20
COLOUR	WHITE	WHITE
ODOUR	NONE	NONE
BULK DENSITY G/L	0.20 – 0.30	0.20 – 0.30
MELTING POINT °C	112- 125	120- 135
WATER CONTENT % MAX.	0.5	0.5

**PACKING:** 210 Litres drums.

**Date of Issue:** 20.12.2014

**Date of revision:** 06.03.2017

**PDS NO.** 08.30.01

These are typical figures and do not constitute a specification. In pursuit of continuous improvement, these figures may be changed without notice at the sole discretion of EASTERN PETROLEUM PVT. LTD.

