

CIN NO:U24100MH1964PTC012931

an ISO 9001-2008 certified company
Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg,
(Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India.
Tel.: +91 - 22 - 4232 4121, 2529 9990,
Email: office@easternpetroleum.in, Web:www.easternpetroleum.in

## **PRODUCT DATA SHEET**

PRODUCT:	WHITE MINERAL OIL		
GRADE:	EASTTO LX-10, LX-15, LX-20, LX-30		
INTRODUCTION:	It is a purified mixture of Liquid Saturated Hydrocarbons, obtained from Petroleum and are highly paraffinic in nature. It is Transparent, Colourless, and Tasteless and odourless liquid. This is highly refined hydro-treated oils having excellent thermal and chemical stability with high flash points.		
APPLICATION:	It is used in the manufacture of Bulk Drugs, Lotions, Textile Auxiliaries, Pharmaceutical products, Agrochemicals, Aerosols, Insecticides, Leather Processing, Dye Intermediates, Protective coating, Personal care product, industrial and automotive Lubricants, Printing inks, Metal working fluid, wire rope lubricants, Die mould industry, Agarbatti industry and Transformer oil . It can be used during processing of Plastics, Mould release agent, Plasticizer and preparation of master batches.		







Used in lotions, lubricants, Mould industries etc.

## **TYPICAL PROPERTIES:**

CHARACTERISTICS	LX-10	LX-15	LX-20	LX-30
APPEARANCE	WATER WHITE	WATER WHITE	WATER WHITE	WATER WHITE
SPECIFIC GRAVITY @ 15°C	0.81	0.83	0.83	0.84
K. VISCOSITY @ 40°C, cst	7.5	15	20	30
FLASH POINT Min °C	140	165	180	200

PACKING: 210 Litres M.S. Barrels / Tanker Loads

Date of issue: 03.01.2015

Date of revision: 03.09.2016

These Characteristics are typical of current production while future production will confirm to **EASTERN PETROLEUM PVT. LTD.** Specification variation in these characteristics may occur.

