

Eastto Hydraulic Oils AW

Grades:

VG 32, 46, 57*, 68, 100 AND 150

Introduction:

Eastto Hydraulic Oils AW are blended from highly refined base stocks with high viscosity index and specially selected anti-oxidant, anticorrosion, anti-wear, anti-rust and anti-foam additives. These oils can sustain very high pressure of the system and high speed of the pumps, and compatible with the seals normally used in the hydraulic system.

Application:

EASTTO HYDRAULIC OILS AW are recommended where long service life and a wide variety of industrial hydraulic and circulation systems are required.

Performance Level: IS: 10522:1983 [Reaffirmed November, 1998]

Typical properties

Characteristics	32	46	57	68	81	100	150
KV at 40°C	30 – 34	46 – 48	54 - 60	66 – 70	78 - 84	95 –105	145-155
VI, Min.	95	95	95	95	95	95	95
Flash Point, COC, °C. Min	190	210	210	210	210	220	220
Pour Point, °C.Max.	-6	-6	-6	-6	-6	-6	-6

Packing: 210 Litres Drum



Eastern Petroleum Private Limited

an ISO 9001-2008 certified company



Eastto Hydraulic Oils AW

Eastern Petroleum Private Limited

Regd. Off.:

Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg,
(Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India.

Tel.: +91 - 22 - 4232 4121, +91 - 22 - 2529 9990

Email: office@easternpetroleum.in, office@eastto.in,

Web: www.easternpetroleum.in, www.eastto.in

